

YASKAWA

AC Drives

Product Range



Yaskawa - Balancing power to perfection

Cost-saving by optimized application
Efficiency

Experience from 30 million
installed AC drives

Application Reliability by 10 years of
maintenance free drive operation

Flexibility to master any challenge

Maximize machine Performance

Ease of use minimizes setup times



At home. In any application.

We have extensive knowledge and many years of experience in automation with more than 30 million AC drives installed worldwide. Thanks to our high manufacturing quality and the design for long, maintenance-free operation, our drives perform their work discretely for many years.

This makes our AC drives special:

Scalable

Embedded programming environment to customize drive functions can replace external controllers.

Common menus

Menus and parameters are arranged and named as with any other Yaskawa drive, thus reducing training expenses.

24 VDC power input for controller

Simplify your wiring and keep your control system operational, even during standby or power outages.

24 VDC power for sensors

Internal power supply delivers an extra 150 mA for use with external sensors, thus eliminating the need for a separate power supply.

Built-in EMC filter

Easy compliance with global standards and simplified machine design due to a reduced number of parts.

Optimal rating

Normal Duty rating allows operation of a motor that is one size larger in variable torque applications.

Predictive maintenance

Service life indicators for main components prevent production losses due to sudden breakdowns.

Our AC drives perform well in many applications, like:



HVAC



Pumps & Fans



Marine



Crane & Hoist



Winders



Metalworking

AC Drives Overview

The background of the slide is a solid blue color with a complex, abstract geometric pattern. The pattern consists of several overlapping, angular shapes in various shades of blue, creating a sense of depth and movement. The shapes are primarily triangular and quadrilateral, with some larger, more irregular polygons. The overall effect is a modern, technical, and professional aesthetic.

GA700

AC Drives for Industrial Applications

| Technical Data | GA700 |
|------------------------------|------------|
| Motor power range [kW] | 0.55 – 355 |
| Induction motor (IM) | √ |
| Permanent magnet motor (PM) | √ |
| Synchronous reluctance motor | √ |

Standard AC Drive

The GA700 precisely controls induction, permanent magnet, and synchronous reluctance motors providing versatility to run a variety of applications with just one drive. The times of complex motor set-up are over. With the new EZ vector mode, the GA700 can run all of these motor types without the need for comprehensive tuning.

Easy Programming

DriveWorksEZ® is our intuitive graphical programming environment. Create customized functions for your application in a very short time by dragging and dropping function blocks. The online diagnosis tool supports testing.

Features

- Easy set-up due to the integrated start-up wizard
- Integrated features (STO with SIL 3, Braking transistor [up to 75 kW], EMC filter, DC reactor [22 kW and above] ...)
- Data logging with real time stamp up to 32 GB on MicroSD card
- Mobile Device Connectivity: Cloud connected DriveWizard Mobile App for drive management on smartphones and tablets, Manual App providing technical documentation exactly where you need it
- Safe programming when switched off
- Network up to five GA700 drives with a single communication card



GA500

AC Drives for Industrial Applications

| Technical Data | GA500 |
|------------------------------|----------|
| Motor power range [kW] | 0.1 – 30 |
| Induction motor (IM) | √ |
| Permanent magnet motor (PM) | √ |
| Synchronous reluctance motor | √ |

Standard AC Drive

Compact in size and flexible in terms of motor type and connectivity, the GA500 is designed to easily master nearly any application.

Easy Programming

DriveWorksEZ® is our intuitive graphical programming environment. Create customized functions for your application in a very short time by dragging and dropping function blocks. The online diagnosis tool supports testing.

Features

- Easy network integration
- Robust design. Operation up to 4000 m altitude and 60 °C environment
- Coated PCBs
- Embedded braking chopper
- Integrated programming environment
- 24 VDC power input for controller
- USB port
- 10 years maintenance-free design
- Screwless control terminals
- Easily accessible mains terminals
- 24 VDC power for sensors
- Built-in EMC filter
- One drive for various applications (induction, permanent magnet and synchronous reluctance motors)



CR700

AC Drives for Crane Applications

Crane AC Drive

Continuous improvements of the key functions for crane applications has won the trust of our customers for over 30 years. The CR700 balances the hoist application in perfection. Made possible by innovative design advantages the CR700 crane drive helps you to lower initial investment for factory construction, supports you by increasing your productivity, lowers the efforts for daily maintenance and helps to reduce energy consumption.



| Technical Data | CR700 |
|------------------------|------------|
| Motor power range [kW] | 0.55 – 315 |
| Induction motor (IM) | ✓ |

Features

- Synchronous position control and tandem application
- Anti-sway function
- Light-load function
- Load balance without encoder
- Wire length monitor
- Maintenance monitor
- Travel limit
- Brake command monitor

J1000, V1000, A1000

The Legacy AC Drives

Standard AC Drive

The 1000-series AC drives have a long history of reliable operation in a huge range of applications. We offer the J1000 compact drive for use with induction motors - you only need to set up a few parameters and you're ready to go. The V1000 is also suitable for PM motors and offers more adjustment possibilities, but is just as compact as the little brother. When you need high output power, or want to use a motor encoder, then the A1000 is your best and most flexible choice.

| Technical Data | J1000 | V1000 | A1000 |
|-----------------------------|-----------|------------|------------|
| Motor power range [kW] | 0.1 – 5.5 | 0.1 – 18.5 | 0.55 – 630 |
| Induction motor (IM) | ✓ | ✓ | ✓ |
| Permanent magnet motor (PM) | - | ✓ | ✓ |



T1000A, T1000V

Multi-Purpose Textile Drives

| Technical Data | T1000A | T1000V |
|-----------------------------|------------|------------|
| Motor power range [kW] | 0.55 – 185 | 0.1 – 18.5 |
| Induction motor (IM) | √ | √ |
| Permanent magnet motor (PM) | √ | √ |

Textile AC Drive

The T1000A is an AC drive with current vector control with or without speed sensor. Thanks to specially coated circuit boards, the reliable power failure bridging or the heat sink and fanless version for mounting on a water cooler, the T1000A is perfectly suited for equipping reliable and durable textile machines.

The T1000V is the compact solution for applications in the textile industry.



T1000A Features

- High-precision open- and closed-loop-control of induction and permanent magnet motors
- Heat sink and cold plate versions for water cooler mounting available
- Integrated textile functions, e.g. for thread laying and power failure detection/treatment
- Very robust drive for harsh environments, designed for 10 years maintenance-free operation
- Built-in maintenance monitors for IGBT, capacitors or operation time
- Built-in SIL2 / PL-d safety

T1000V Features

- Encoderless control of asynchronous and PM motors
- Heat sink and cold plate versions for water cooler mounting available
- Specially coated PCBs for textile applications
- Compact and cost effective textile solution
- Built-in maintenance monitors for IGBT, capacitors, fan and charging circuit
- Very robust AC drive designed for 10 years continuous and maintenance-free operation

L1000A, LA500

Standard Drives for Lift Applications

| Technical Data | L1000A | LA500 |
|-----------------------------|-----------|----------|
| Motor power range [kW] | 1.5 – 110 | 4.0 – 22 |
| Induction motor (IM) | √ | √ |
| Permanent magnet motor (PM) | √ | - |

Lift AC Drive

The L1000A lift drive is the perfect solution for technical requirements of today's lifts. L1000A controls induction and permanent magnet motors and is the first choice for new installations, machine room less lifts and lift modernization.

The compact LA500 is the economic solution for modernization and new installation of lifts with gear box motors without speed feedback. By sticking to the basics, this AC drive combines usability and outstanding ride performance with a robust and durable design.

L1000A Features

- Open- and closed-loop-control for IM and PM motors
- Large power range
- Programming in lift terminology and in 13 languages
- Displays parameter in lift-specific terms and units (m/s, m/s² ...)
- Automatic evacuation with UPS system/battery
- Flexible controller interface
- Best ride comfort
- Operation without motor contactors (SIL3 STO)
- DCP3/DCP4/CANLift

LA500 Features

- Open- and closed-loop-control for induction motors
- Programming in lift terminology and in 8 languages
- State-of-the-art motor control algorithms for a smooth ride and a precise stop
- Designed for long performance and low life-cycle cost
- Preventive maintenance indicator for IGBT, capacitors and cooling fans



Green Performance Solutions

| Model | R1000 | D1000 | U1000 |
|---|-------|-------|-------|
| Energy saving by braking power regeneration | ● | ● | ● |
| Motor drive | – | – | ● |
| Improve power factor | – | ● | ● |
| Suppress input current harmonics | – | ● | ● |
| DC voltage boost | – | ● | – |
| Feed-in of multiple drives | ○ | ● | – |
| Simple wiring | ○ | ○ | ● |
| Downsize panel | ○ | ○ | ● |
| Integrated Bypass function at 50 Hz | – | – | ● |

R1000

Energy Saving Regenerative Unit

Intelligent Braking Resistor

The R1000 regenerative unit replaces conventional braking resistors in machines and systems and makes braking energy available to other consumers in the same system. This saves energy and reduces costs.

Features

- Allows 4-quadrant-operation without braking resistors
- No wasted heat due to braking resistors, thus less need for cooling/ventilation, reduced fire hazard and operating costs
- Provides regenerative energy for other consumers in the plant, reducing total power consumption
- Quick amortisation of investments

| Technical Data | R1000 |
|----------------------------|-----------|
| Regeneration capacity [kW] | 3.5 – 300 |
| Apply to multiple drives | √ |



D1000

Regenerative Converter Unit With Low Harmonics

| Technical Data | D1000 |
|--------------------------------|-----------|
| Power range [kW] | 5.0 – 630 |
| Supress power supply harmonics | √ |
| Apply to multiple drives | √ |

Low Harmonic Energy Recovery Unit

D1000 is a regenerative unit for DC power supply of single drives or systems consisting of AC drives, servos or robots. In addition to the use of braking energy, the D1000 enables particularly efficient and network-friendly system operation.

Features

- 4-quadrant-operation without braking resistors
- Sinusoidal input current (total harmonic distortion < 5 %) and cosphi =1 minimize losses in cables, transformers and generators and allow an optimal utilization of the system
- Controlled, customizable DC voltage guarantees the same level of DC voltage independent of the power supply voltage (Boost function)
- D1000 reduces the cost for energy and maintenance, which allows for a short payback period
- No wasted heat due to braking resistors, thus less need for cooling/ventilation, reduced fire hazard and operating costs



U1000

The AC-to-AC drive For Maximum Efficiency

Matrix Converter

The U1000 is a highly efficient AC drive based on latest Matrix converter technology. With full power regeneration capability it offers great energy saving potential while sinusoidal input currents and a power factor close to one reduce stress on grid components, cables and wires. With an ultra-compact shape, it is the first choice for innovative, energy-efficient drive solutions with or without power regeneration.



Features

- Innovative Matrix Drive technology without DC bus capacitors up to 500 kW
- Built-in power regeneration
- Extremely compact compared to conventional solutions for feedback or low harmonics
- Completely integrated solution minimizes installation and wiring effort
- Built-in bypass operation at 50 Hz for IM motor
- Maximum flexibility through integrated PLC functionality
- Low-loss and smooth system operation thanks to sinusoidal input current and cosphi of almost 1
- Built-in SIL3 STO function for machine safety
- Induction motor and permanent magnet motor control
- Approved for global marine installation

| Technical Data | U1000 |
|----------------------------------|----------------------------------|
| Power range [kW] | 4.0 – 500 |
| Supress power supply harmonics | √ |
| Apply multiple drives | √ |
| Induction and PM motor control | √ |
| Approved for marine installation | BV, ABS, ClassNK, LR, DNV GL, KR |

Easy engineering and customization

The GA500 and GA700 drives come with powerful yet intuitive engineering tools that help minimize setup time while also offering great potential for simplification of machinery and installations.

DriveWizard® 10

DriveWizard® 10 enables easy configuration of GA500 drives. Its comprehensive monitoring functions and integrated oscilloscope allow easy process optimization and fast troubleshooting.

- Connect to the GA500 via USB – even without mains power!
- Configure the GA500 online or offline.
- Log your process with up to six channels of recorded data.
- Create reports to export and send via email.
- Simplify operation and save valuable time during setup, maintenance, or troubleshooting.
- Import and export data with DriveWizard mobile.
- Connect to multiple drives through ProfiNet, EtherNet/IP or Modbus TCP.



DriveWorksEZ® 10

DriveWorksEZ® is an icon-based, drag-and-drop graphical environment for adding programmable functions allowing the drive to be tailored for a variety of machine and application requirements without the cost of external controllers, such as PLCs or additional controller hardware options.

- Select from 400+ function blocks
- Logic/math functions
- Timers/counters
- Up to 100 connections
- Offline simulation mode for testing without the risk of application malfunctions
- Protection of intellectual property with project lock
- Online monitor for visual debugging
- Fast cycle time of 2 ms, independent of program size



DriveWorks Application Library

The DWEZ Application Library provides pre-configured applications that can be used instantly or can be modified and expanded to fit the need of your application or machine.

These are just a few of the applications available:

- Brake sequence
- Flexible timer
- Torque limits
- Master-Slave via serial communication without PLC
- Dual PI controller
- Unbalance detection

Always handy

Anything needed to operate a GA500 or a GA700 fits in your pocket. The DriveWizard® mobile and the Manuals App turn your smartphone or tablet into a versatile and indispensable toolbox.

DriveWizard Mobile

DriveWizard mobile is the ultimate setup tool for GA500 drives. From simple parameter editing through Setup Wizard with an 8 channel fully featured oscilloscope, it provides all tools needed for setup, monitoring and process optimization.

- Intuitive parameter editing with help and search function
- Create favorite parameter lists
- 8-channel oscilloscope with comprehensive trigger functions and data analysis
- Parameter backup/verify
- Setup Wizard for quick setup without knowledge about menus and parameters
- Troubleshooting support with fault analysis and countermeasures
- Export to DriveWizard PC tool
- Worry-free data recovery: Parameter back-up/retrieval anytime via Yaskawa cloud service for registered drives
- Usable offline in areas without mobile reception

Yaskawa Manuals app

Never carry heavy paper manuals again. With the Yaskawa Manuals app the latest manuals for GA500 and GA700 drives are always with you.

- Responsive layout - line breaks automatically adjust to zoom level for best readability without panning left/right
- Quickly find the information you really need using the search function
- Set own bookmarks to frequently used pages
- All books can be downloaded for offline use
- Always up-to-date documents







Mobile device connectivity is achieved through using the built-in USB port (USB on-the-go) or wireless communication with the Bluetooth® LCD keypad option.

Bluetooth® and the Bluetooth logo are registered trademarks of Bluetooth SIG, Inc. USA. Android™ is a trademark of Google Inc. iOS® is a registered trademark of Cisco and is used under license by Apple, Inc.













AC Drives Comparison

| | GA700 | GA500 | CR700 |
|---|---|--|---|
| Type |  |  |  |
| Max. motor output | | | |
| 1-phase AC | – | 230 V AC 0.1 - 4.0 kW | – |
| 3-phase AC | 200 V AC 0.55 - 110 kW | 200 V AC 0.1 - 22 kW | 200 V AC 0.55 - 110 kW |
| | 400 V AC 0.55 - 355 kW | 400 V AC 0.37 - 30 kW | 400 V AC 0.55 - 355 kW |
| Applicable motor | | | |
| Induction motor with/without encoder | ●/● | –/● | ●/● |
| Permanent magnet motor with/without encoder | ●/● | –/● | –/– |
| Synchronous reluctance motor | ● | ● | – |
| Cooling method | | | |
| Air cooling | ● | ● | ● |
| Coldplate | – | ◇ | – |
| Torque control | ● | ● (using DriveWorksEZ) | ● |
| Braking chopper built-in | ● (up to 75 kW) | ● | ● (up to 75 kW) |
| Max. output frequency | 590 Hz | 590 Hz / ◇ 2000 Hz | 590 Hz |
| I/O built-in | | | |
| Analog input/output | 3/2 | 2/1 | 3/2 |
| Digital input/output | 8/4 | 7/3 | 8/4 |
| Motor thermal protection | ● | ● | ● |
| Fieldbus | | | |
| RS-422/485 (Memobus/Modbus) | ● (RS-485) | ● (RS-485) | ● (RS-485) |
| RS-232C | ● | ● | ● |
| Mechatrolink-III | ◇ | ◇ | ◇ |
| Ethernet/IP | ◇ | ◇ | ◇ |
| EtherCAT | ◇ | ◇ | ◇ |
| Modbus TCP | ◇ | ◇ | ◇ |
| Profinet | ◇ | ◇ | ◇ |
| CC-Link | ◇ | ◇ | ◇ |
| DeviceNet | ◇ | ◇ | ◇ |
| Profibus-DP | ◇ | ◇ | ◇ |
| CANopen | ◇ | ◇ | ◇ |
| Powerlink | ◇ | ◇ | ◇ |

| | GA700 | GA500 | CR700 |
|-----------------------------------|---|--|---|
| Type |  |  |  |
| Functions | | | |
| Energy saving | • | • | • |
| Dual Rating (ND/HD) | • | • | • |
| Speed search | • | • | • |
| PID control (with sleep function) | • | • | • |
| Momentary power loss ride-thru | • | • | • |
| Application parameter presets | • | • | • |
| Predictive maintenance functions | • | • | • |
| USB interface | • | • | • |
| Coated PCB | • | • | • |
| External 24 V power supply input | • | • | • |
| PLC function (DriveWorksEZ) | • | • | • |
| Functional safety options | | | |
| Safety | SIL3/PL e | SIL3/PL e | SIL3/PL e |
| Standards | | | |
| CE/RoHS | •/• | •/• | •/• |
| UL/cUL/UL508C | • | • | • |
| Marine (GL) | – | – | – |




AC Drives Comparison

| | A1000 | V1000 | J1000 | T1000A | T1000V |
|---|---|---|--|---|---|
| Type |  |  |  |  |  |
| Max. motor output | | | | | |
| 1-phase AC | – | 230 V AC 0.1 - 4.0 kW | 230 V AC 0.1 - 2.2 kW | – | 230 V AC 0.1 - 4.0 kW |
| 3-phase AC | 200 V AC 0.55 - 110 kW | 200 V AC 0.1 - 18.5 kW | 200 V AC 0.1 - 5.5 kW | 200 V AC 0.55 - 110 kW | 200 V AC 0.1 - 18.5 kW |
| | 400 V AC 0.55 - 630 kW | 400 V AC 0.2 - 18.5 kW | 400 V AC 0.2 - 5.5 kW | 400 V AC 0.55 - 185 kW | 400 V AC 0.1 - 18.5 kW |
| Applicable motor | | | | | |
| Induction motor with/without encoder | ●/● | –/● | –/● | ●/● | –/● |
| Permanent magnet motor with/without encoder | ●/● | –/● | –/– | ●/● | –/● |
| Synchronous reluctance motor | – | – | – | – | – |
| Cooling method | | | | | |
| Air cooling | ● | ● | ● | ● | ● |
| Coldplate | ◇ | ◇ | – | ◇ | ◇ |
| Torque control | ● | – | – | ● | – |
| Braking chopper built-in | ● (up to 30 kW) | ● | ● | ● | ● |
| Max. output frequency | 400 Hz / ◇ 1000 Hz | 400 Hz / ◇ 1000 Hz | 400 Hz | 400 Hz | 400 Hz |
| I/O built-in | | | | | |
| Analog input/output | 3/2 | 2/1 | 1/1 | 3/2 | 2/1 |
| Digital input/output | 8/4 | 6/3 | 5/1 | 8/4 | 6/3 |
| Motor thermal protection | ● | ● | ● | ● | ● |
| Fieldbus | | | | | |
| RS-422/485 (Memobus/Modbus) | ● | ● | ◇ | ● | ● |
| RS-232C | ● | ● | ◇ | ● | ● |
| Mechatrolink-III | ◇ | ◇ | – | ◇ | ◇ |
| Ethernet/IP | ◇ | ◇ | – | – | – |
| EtherCAT | ◇ | ◇ | – | – | – |
| Modbus TCP | ◇ | ◇ | – | ◇ | ◇ |
| Profinet | ◇ | ◇ | – | – | – |
| CC-Link | ◇ | ◇ | – | ◇ | ◇ |
| DeviceNet | ◇ | ◇ | – | – | – |
| Profibus-DP | ◇ | ◇ | – | ◇ | ◇ |
| CANopen | ◇ | ◇ | – | ◇ | ◇ |
| Powerlink | ◇ | ◇ | – | ◇ | ◇ |

| | A1000 | V1000 | J1000 | T1000A | T1000V |
|-----------------------------------|---|---|--|---|---|
| Type |  |  |  |  |  |
| Functions | | | | | |
| Energy saving | • | • | – | • | • |
| Dual Rating (ND/HD) | • | • | • | • | • |
| Speed search | • | • | – | • | • |
| PID control (with sleep function) | • | • | – | • | • |
| Momentary power loss ride-thru | • | • | • | • | • |
| Application parameter presets | • | • | – | – | – |
| Predictive maintenance functions | • | • | • | • | • |
| USB interface | • | – | – | • | – |
| Coated PCB | ◊ | ◊ | – | • | • |
| External 24 V power supply input | ◊ | ◊ | – | ◊ | ◊ |
| PLC function (DriveWorksEZ) | • | • | – | – | – |
| Functional safety options | | | | | |
| Safety | SIL2/PL d | SIL2/PL d | – | SIL2/PL d | SIL2/PL d |
| Standards | | | | | |
| CE/RoHS | •/• | •/• | •/• | •/• | •/• |
| UL/cUL/UL508C | • | • | • | • | • |
| Marine (GL) | • | – | – | – | – |


Regenerative Units Comparison

| | U1000 | D1000 | R1000 |
|---|---|---|---|
| Type |  |  |  |
| Max. motor output | | | |
| 1-phase AC | – | – | – |
| 3-phase AC | 200 V AC 5.5 - 55 kW | 200 V AC 5.0 - 130 kW | 200 V AC 3.5 - 105 kW |
| | 400 V AC 3.9 - 500 kW | 400 V AC 5.0 - 630 kW | 400 V AC 3.5 - 300 kW |
| Applicable motor | | | |
| Induction motor with/without encoder | ●/● | –/– | –/– |
| Permanent magnet motor with/without encoder | ●/● | –/– | –/– |
| Synchronous reluctance motor | – | – | – |
| Cooling method | | | |
| Air cooling | ● | ● | ● |
| Coldplate | – | – | – |
| Torque control | ● | – | – |
| Braking chopper built-in | Not required | – | – |
| Max. output frequency | 400 Hz | – | – |
| I/O built-in | | | |
| Analog input/output | 3/2 | 3/2 | 3/2 |
| Digital input/output | 8/4 | 8/4 | 8/4 |
| Motor thermal protection | ● | – | – |
| Fieldbus | | | |
| RS-422/485 (Memobus/Modbus) | ● | ● | ● |
| RS-232C | ● | ● | ● |
| Mechatrolink-III | ◇ | ◇ | ◇ |
| Ethernet/IP | ◇ | ◇ | ◇ |
| EtherCAT | ◇ | ◇ | ◇ |
| Modbus TCP | ◇ | ◇ | ◇ |
| Profinet | ◇ | ◇ | ◇ |
| CC-Link | ◇ | ◇ | ◇ |
| DeviceNet | ◇ | ◇ | ◇ |
| Profibus-DP | ◇ | ◇ | ◇ |
| CANopen | ◇ | ◇ | ◇ |
| Powerlink | ◇ | ◇ | ◇ |

| | U1000 | D1000 | R1000 |
|-----------------------------------|---|---|---|
| Type |  |  |  |
| Functions | | | |
| Energy saving | • | – | – |
| Dual Rating (ND/HD) | • | – | – |
| Low harmonics (THDi < 5 %) | • | • | – |
| Power regeneration operation | • | ‡ | ‡ |
| Speed search | • | – | – |
| PID control (with sleep function) | • | – | – |
| Momentary power loss ride-thru | – | • | – |
| Application parameter presets | • | – | – |
| Predictive maintenance functions | • | • | • |
| USB interface | • | • | • |
| Coated PCB | • | – | – |
| External 24 V power supply input | ◊ | ◊ | ◊ |
| PLC function (DriveWorksEZ) | • | – | – |
| Functional safety options | | | |
| Safety | (SIL3/PL e) | – | – |
| Standards | | | |
| CE/RoHS | •/• | •/• | •/• |
| UL/cUL/UL508C | • | • | • |
| Marine (GL) | • | – | – |



Lift Drives Comparison

| | L1000A | LA500 |
|---|---|---|
| Type |  |  |
| Max. motor output | | |
| 3-phase AC | 200 V AC 1.5 - 110 kW 400 V AC 1.5 - 110 kW | 200 V AC 4.0 - 18.5 kW 400 V AC 4.0 - 22 kW |
| Motor | | |
| Induction motor with/without encoder | ●/● | -/● |
| Permanent magnet motor with/without encoder | ●/- | -/- |
| Cooling method | | |
| Air cooling | • | • |
| Braking chopper built-in | • (up to 22kW) | • |
| Max. output frequency | 200 Hz | 120 Hz |
| I/O built-in | | |
| Analog input/output | 2/2 | -/1 |
| Digital input/output | 8/6 | 7/3 |
| Motor thermal protection | • | • |
| Fieldbus | | |
| RS-422/485 (Memobus/Modbus) | • | - |
| RS-232C | • | • |
| CANopen | ◇ CANopen-Lift | - |
| DCP3/DCP4 | • | - |
| Functions | | |
| Energy saving | • | - |
| Predictive maintenance functions | • | • |
| USB interface | - | • |
| Battery rescue operation/UPS | • | • |
| External 24 V power supply unit | ◇ | • |
| Brake sequence | • | • |
| Short floor operation | • | • |
| Elevator units | • | • |
| Functional safety options | | |
| Safe Torque Off | • SIL2/PL d / ◇ SIL3/PL e | SIL3/PL e |
| Standards | | |
| CE/RoHS | ●/● | ●/● |
| UL/cUL/UL508C | • | • |
| Lift Standard EN81 | • | • |

YASKAWA Europe GmbH

Philipp-Reis-Str. 6
65795 Hattersheim am Main
Germany

+49 6196 569-500
support@yaskawa.eu
www.yaskawa.eu.com

02/2023
YEU_INV_Range_EN_v11

Specifications are subject to change without notice for ongoing product modifications and improvements. © YASKAWA Europe GmbH. All rights reserved.

YASKAWA